

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Substance
Trade name	: ResiGlass 50 Epoxy Casting Resin Deep Pour Part B
Product code	: H5244

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category	: Industrial use, Professional use
Use of the substance/mixture	: Casting compound

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Resins 'R' Us UK Ltd
 High House Farm Lane,
 Colton, Norwich, NR9 5DG
 United Kingdom
 T +44 (0) 1508 500888
sales@resinsrus.co.uk - www.resinsrus.co.uk

1.4. Emergency telephone number

Emergency number	: +44 (0) 1926 641 600
	Office hours only (08:30 - 17:00)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4	H302
Acute toxicity (dermal), Category 4	H312
Skin corrosion/irritation, Category 1	H314
Serious eye damage/eye irritation, Category 1	H318
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Harmful in contact with skin. Harmful if swallowed. Causes severe skin burns and eye damage. Causes serious eye damage. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS05

GHS07

GHS09

Signal word (CLP)

: Danger

Hazard statements (CLP)

: H302+H312 - Harmful if swallowed or in contact with skin.

H314 - Causes severe skin burns and eye damage.

H411 - Toxic to aquatic life with long lasting effects.

ResiGlass 50 Epoxy Casting Resin Deep Pour Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Precautionary statements (CLP)

: P264 - Wash hands thoroughly after handling.
P280 - Wear eye protection, protective clothing, protective gloves.
P303+P361+P353+P310 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a POISON CENTER or doctor.
P305+P351+P338+P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P391 - Collect spillage.

2.3. Other hazards

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Name : H5244

Name	Product identifier	%
Propylidynetrimethanol, propoxylated, reaction products with ammonia [1 - 6.5 moles propoxylated]	CAS-No.: 39423-51-3 EC-No.: 500-105-6 REACH-no: 01-2119556886-20	100

3.2. Mixtures

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Burns.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

ResiGlass 50 Epoxy Casting Resin Deep Pour Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin, eyes and clothing. Do not breathe dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.
Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Do not get in eyes, on skin, or on clothing. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray.
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

No additional information available

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

ResiGlass 50 Epoxy Casting Resin Deep Pour Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Odour	: Amine-like.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: < -20 °C
Boiling point	: Not available
Flammability	: Not applicable
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 218.5 °C (closed cup)
Auto-ignition temperature	: 320 °C
Decomposition temperature	: 236 °C
pH	: 11.6
pH solution	: 50 g/l
Viscosity, kinematic	: 110 mm²/s
Viscosity, dynamic	: 60 – 80 mPa·s (25°C)
Solubility	: Water: 562 g/l (20°C)

ResiGlass 50 Epoxy Casting Resin Deep Pour Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Partition coefficient n-octanol/water (Log Kow)	:	Not available
Partition coefficient n-octanol/water (Log Pow)	:	-1.13 (20°C)
Vapour pressure	:	0.0023 Pa (20°C)
Vapour pressure at 50°C	:	Not available
Density	:	0.95 – 1 g/cm³ (25°C)
Relative density	:	Not available
Relative vapour density at 20°C	:	1
Particle characteristics	:	Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	:	Harmful if swallowed.
Acute toxicity (dermal)	:	Harmful in contact with skin.
Acute toxicity (inhalation)	:	Not classified

Propylidynetrtrimethanol, propoxylated, reaction products with ammonia [1 - 6.5 moles propoxylated] (39423-51-3)

LD50 oral rat	550 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), 95% CL: 123,9 - 3930
LD50 dermal rat	> 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EPA OPPTS 870.1200 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal)), Remarks on results: other:

Skin corrosion/irritation : Causes severe skin burns.
pH: 11.6

Propylidynetrtrimethanol, propoxylated, reaction products with ammonia [1 - 6.5 moles propoxylated] (39423-51-3)

pH	11.6 (50g/l)
----	--------------

ResiGlass 50 Epoxy Casting Resin Deep Pour Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Serious eye damage/irritation : Causes serious eye damage.
pH: 11.6

Propylidynetrimethanol, propoxylated, reaction products with ammonia [1 - 6.5 moles propoxylated] (39423-51-3)

pH	11.6 (50g/l)
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

Propylidynetrimethanol, propoxylated, reaction products with ammonia [1 - 6.5 moles propoxylated] (39423-51-3)

NOAEL (oral, rat, 90 days)	≥ 100 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	> 160 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study), Remarks on results: not determinable
Aspiration hazard	: Not classified

Hardener H5244

Viscosity, kinematic	110 mm ² /s
----------------------	------------------------

Propylidynetrimethanol, propoxylated, reaction products with ammonia [1 - 6.5 moles propoxylated] (39423-51-3)

Viscosity, kinematic	110 mm ² /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm ² /s)'
----------------------	---

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term : Not classified
(acute)
Hazardous to the aquatic environment, long-term : Toxic to aquatic life with long lasting effects.
(chronic)
Not rapidly degradable

Propylidynetrimethanol, propoxylated, reaction products with ammonia [1 - 6.5 moles propoxylated] (39423-51-3)

LC50 - Fish [1]	> 100 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	13 mg/l Test organisms (species): Daphnia magna
ErC50 algae	4.4 mg/l Selenastrum capricornutum
NOEC chronic algae	1 mg/l Selenastrum capricornutum

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Hardener H5244

Partition coefficient n-octanol/water (Log Pow)	-1.13 (20°C)
---	--------------

ResiGlass 50 Epoxy Casting Resin Deep Pour Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Propylidynetrimethanol, propoxylated, reaction products with ammonia [1 - 6.5 moles propoxylated] (39423-51-3)

Partition coefficient n-octanol/water (Log Pow)	-1.13 (20 - 25°C)
---	-------------------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods

HP Code

- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : HP6 - "Acute Toxicity:" waste which can cause acute toxic effects following oral or dermal administration, or inhalation exposure.
- : HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.
- : HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 2735	UN 2735	UN 2735	UN 2735	UN 2735
14.2. UN proper shipping name				
POLYAMINES, LIQUID, CORROSIVE, N.O.S. (Propylidynetrimethanol, propoxylated, reaction products with ammonia [1 - 6.5 moles propoxylated])	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (Propylidynetrimethanol, propoxylated, reaction products with ammonia [1 - 6.5 moles propoxylated])	Polyamines, liquid, corrosive, n.o.s. (Propylidynetrimethanol, propoxylated, reaction products with ammonia [1 - 6.5 moles propoxylated])	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (Propylidynetrimethanol, propoxylated, reaction products with ammonia [1 - 6.5 moles propoxylated])	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (Propylidynetrimethanol, propoxylated, reaction products with ammonia [1 - 6.5 moles propoxylated])
Transport document description				
UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (Propylidynetrimethanol, propoxylated, reaction products with ammonia [1 - 6.5 moles propoxylated]), 8, II, (E), ENVIRONMENTALLY HAZARDOUS	UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (Propylidynetrimethanol, propoxylated, reaction products with ammonia [1 - 6.5 moles propoxylated]), 8, II, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 2735 Polyamines, liquid, corrosive, n.o.s. (Propylidynetrimethanol, propoxylated, reaction products with ammonia [1 - 6.5 moles propoxylated]), 8, II, ENVIRONMENTALLY HAZARDOUS	UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (Propylidynetrimethanol, propoxylated, reaction products with ammonia [1 - 6.5 moles propoxylated]), 8, II, ENVIRONMENTALLY HAZARDOUS	UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (Propylidynetrimethanol, propoxylated, reaction products with ammonia [1 - 6.5 moles propoxylated]), 8, II, ENVIRONMENTALLY HAZARDOUS

ResiGlass 50 Epoxy Casting Resin Deep Pour Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
14.3. Transport hazard class(es)				
8	8	8	8	8
14.4. Packing group				
II	II	II	II	II
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
Marine pollutant: Yes				
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	:	C7
Special provisions (ADR)	:	274
Limited quantities (ADR)	:	1I
Excepted quantities (ADR)	:	E2
Packing instructions (ADR)	:	P001, IBC02
Mixed packing provisions (ADR)	:	MP15
Portable tank and bulk container instructions (ADR)	:	T11
Portable tank and bulk container special provisions (ADR)	:	TP1, TP27

Tank code (ADR)	:	L4BN
Vehicle for tank carriage	:	AT
Transport category (ADR)	:	2
Hazard identification number (Kemler No.)	:	80
Orange plates	:	

Tunnel restriction code (ADR)

:

EAC code

:

Transport by sea

Special provisions (IMDG)	:	274
Limited quantities (IMDG)	:	1 L
Excepted quantities (IMDG)	:	E2
Packing instructions (IMDG)	:	P001
IBC packing instructions (IMDG)	:	IBC02
Tank instructions (IMDG)	:	T11
Tank special provisions (IMDG)	:	TP1, TP27
EmS-No. (Fire)	:	F-A
EmS-No. (Spillage)	:	S-B
Stowage category (IMDG)	:	A
Segregation (IMDG)	:	SGG18, SG35
Properties and observations (IMDG)	:	Colourless to yellowish liquids or solutions with a pungent odour. Miscible with or soluble in water. When involved in a fire, evolve toxic gases. Corrosive to most metals, especially to copper and its alloys. Reacts violently with acids. Cause burns to skin, eyes and mucous membranes.

ResiGlass 50 Epoxy Casting Resin Deep Pour Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Air transport

PCA Excepted quantities (IATA)	:	E2
PCA Limited quantities (IATA)	:	Y840
PCA limited quantity max net quantity (IATA)	:	0.5L
PCA packing instructions (IATA)	:	851
PCA max net quantity (IATA)	:	1L
CAO packing instructions (IATA)	:	855
CAO max net quantity (IATA)	:	30L
Special provisions (IATA)	:	A3, A803
ERG code (IATA)	:	8L

Inland waterway transport

Classification code (ADN)	:	C7
Special provisions (ADN)	:	274
Limited quantities (ADN)	:	1 L
Excepted quantities (ADN)	:	E2
Carriage permitted (ADN)	:	T
Equipment required (ADN)	:	PP, EP
Number of blue cones/lights (ADN)	:	0

Rail transport

Classification code (RID)	:	C7
Special provisions (RID)	:	274
Limited quantities (RID)	:	1L
Excepted quantities (RID)	:	E2
Packing instructions (RID)	:	P001, IBC02
Mixed packing provisions (RID)	:	MP15
Portable tank and bulk container instructions (RID)	:	T11
Portable tank and bulk container special provisions (RID)	:	TP1, TP27
Tank codes for RID tanks (RID)	:	L4BN
Transport category (RID)	:	2
Colis express (express parcels) (RID)	:	CE6
Hazard identification number (RID)	:	80

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Not listed on REACH Annex XVII

REACH Annex XIV (Authorisation List)

Not listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Not listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Not listed on the PIC list (Regulation EU 649/2012)

POP Regulation (Persistent Organic Pollutants)

Not listed on the POP list (Regulation EU 2019/1021)

Ozone Regulation (1005/2009)

Not listed on the Ozone Depletion list (Regulation EU 1005/2009)

ResiGlass 50 Epoxy Casting Resin Deep Pour Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant

ResiGlass 50 Epoxy Casting Resin Deep Pour Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:

ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H411	Toxic to aquatic life with long lasting effects.
Skin Corr. 1	Skin corrosion/irritation, Category 1

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.